

Accessories for

REVOLUTION™ AND MAVERICK®

The standard Revolution™ and Maverick® tire changers come equipped to handle virtually all tire and wheel combinations.

A	RP6-3784	Paste
B	RP6-1506	Paste brush
C	69-1394-2	Pin protector
D	221-759-2	Valve core remover
E	221-659-2	Bead starting tool
F	RP11-2020688	Valve puller
G	192-233-1	In-between cone
H	192-223-2	Small polymer cone
I	192-226-1	Double-sided polymer cone
J	111-154-1	Spare roller
K	221-810-2	SmartSet mount head (TCM only)
L	179-15-2	Glasses
M	221-713-2	Polymer mount head
N	69-1392-2	Rubber platen cover
O	213-58-1	Mirror (TCM only) (not pictured)



The following options can be used to enhance serviceability of specialized applications.



Flange plate kit – 20-3158-1

Ideal for plastic clad wheels or reverse wheels where maximum protection is needed. Diameter range 98 to 240 mm.

Standard with TCRH, compatible with TCX51C



Flange plate accessory pin kit – 20-3675-1

For wheels with extreme lug hole and lug depth variances.



Dual wheel adaptor – 20-2964-1

Optional adaptor adds clamping capability for dual wheels, 19.5 in. wheels and other wheels with large center holes.



Specialty pin kit – 20-3877-1

Pins have rounded tips for spherical lug seats and are shorter to reduce stack height for reverse applications.



Thick bead kit – 20-3160-1

Wider hook for thicker beads. Suitable for skid steer, load range G-H-J-tires. Plus, reverse wheel plate for 19.5- and 17.5-in. rims.



Under-wheel light kit – 20-4153-1

Illuminates bottom bead for easier bead breaking and lubrication.

Compatible with TCM only, S/N EJC1384 and newer.



TCRH



TCMPRO