

Standard Accessories

The standard Maverick™ tyre changer comes equipped to handle virtually all tyre and wheel combinations.

A	RP6-3784	Paste
B	RP6-1506	Paste brush
C	69-1394-2	Pin protector (2)
D	221-759-2	Valve core remover
E	221-659-2	Bead starting tool
F	RP11-2020688	Valve puller
G	192-233-1	In-between cone (2)
H	192-225-1	Small polymer cone (2)
I	192-226-1	Double-sided polymer cone (2)
J	111-154-1	Spare roller
K	179-15-2	Glasses
L	221-810-2	Polymer mount head (2)
M	69-1392-2	Rubber platten cover (2)



Optional Accessories

The following options can be used to enhance serviceability of specialized applications.



Flange plate kit — 20-3158-1

Ideal for plastic clad wheels or reverse wheels where maximum protection is needed. Maximum diameter 240 mm.



Dual wheel adaptor — 20-2964-1

Optional adaptor adds clamping capability for dual wheels, 19.5 in. wheels, and wheels with large center holes.



Thick bead kit — 20-3160-1

Wider hook for thicker beads. Suitable for skid steer, load range G-H-J-tyres. Plus, reverse wheel plate for 19.5- and 17.5-in. rims.



Flange plate accessory pin kit — 20-3675-1

For wheels with extreme lug hole and lug depth variances. 48.3 mm minimum length pins included. Extensions add 30.5 mm, for a total pin length of 129.5 mm.

Compact wheel lift — 20-3884-1

- ✓ Lifts the heaviest assemblies with ease
- ✓ Auto lowering saves time and prevents damage
- ✓ Configurable pedal operation

