

TCX HD TIRE CHANGER SPECIFICATIONS

	TCX635HD/TCX635PHD*	TCX645HD	TCX660HD
Power Requirements	208-240V, 1 ph, 50 or 60 Hz, 20A NEMA L6-20P	230V +/-10%, 3 ph, 50 or 60 Hz, 26A	220V, 3 ph, 50Hz, 400V, 3 ph, 50Hz
Max. Tire Diameter	58 in (1,473 mm)	90.5 in. (2299 mm)	102.4 in. (2600 mm)
Max. Wheel Width	27 in (686 mm)	42 in. (1067 mm)	59 in. (1498 mm)
Max. Wheel Weight	700 kg (1545 lbs)	1000 kg (2200 lbs)	5511 lbs (2500 kg)
Min. Rim-Center Hole Dia.	100 mm (3.94 in)	100 mm (3.94 in.)	100 mm (3.94 in.)
Rim Diameter Range	14.5 - 24.5 in (368 - 622 mm)	14-46 in. (356-1168 mm) (56 in. (1422 mm) with optional accessories)	14 - 56 in. (356 - 1422 mm)
Match Mounting Capable	Yes	Yes	—
Torque	2203 N-m (1625 ft-lbs)	Low: 4300 N-m (3172 ft-lbs) High: 3000 N-m (2213 ft-lbs)	5150 N-m (3799 ft-lbs)
Rotation Speed	9 rpm clockwise and counter-clockwise	Low speed: 5 rpm High speed: 10 rpm	Low speed: 5 rpm High speed: 10 rpm
Shipping Weight	530 kg (1168 lbs)	740 kg (1631 lbs)	1610 kg (3550 lbs)
Width (W)	2,184 mm (86 in)	2032 - 2388 mm (80 - 94 in)	2442 mm (97 in)
Height (H)	1016 - 1,321 mm (40 - 52 in)	940 - 1550 mm (37 - 61 in)	3022 mm (119 in)
Depth (D)	711 - 1,651 mm (28 - 65 in)	1626 - 2108 mm (64 - 83 in)	2030 mm (80 in)

*TCX635PHD has the same specifications as TCX635HD but also includes mount lever, two ramps, and aluminum jaw covers



TCX635PHD



TCX645HD



TCX660HD

FOR TRACTOR,
IMPLEMENT,
AND OTHER
SPECIALTY WHEEL
ASSEMBLIES

Your Hunter distributor is ready to help

- ✂ Receive same- or next-day service
- 📞 Get a free quote or on-site demo
- 📅 Register for training courses
- 📖 General information and questions



Contact your
local distributor

hunter.com/contact



Because of continuing technological advances, specifications, models and options are subject to change without notice.

HUNTER
Engineering Company

www.hunter.com

11250 Hunter Drive, Bridgeton, MO 63044, USA
Tel: 1-314-731-3020, Fax: 1-314-731-0132
Email: international@hunter.com